

ITEMS	SPECIFICATIONS
Model	HCL WINBee 4000 BVX
Operating System	LINUX Embedded
Chipset	VIA CN896
Processor	VIA C7 1.6GHz
System Memory	Single DDR Slot which supports 512MB DDR 2 RAM upgradable upto 2GB.
Video Graphics	32 MB Shared VRAM
IDE Channel	2 IDE 40 Pin, Each IDE supports 4 GB
Hard Disk Drive	1 GB IDE Flash, Supports upto 4 GB
Protocol Support	RDP, ICA, Telnet, Optional Terminal Emulation Support
Network Interface	10/100/1000Mbps BaseT Fast Ethernet, twisted pair (RJ-45), TCP/ IP with DNS, DHCP and SNMP support, PPP Support, VPN networking support, PPPoE networking support, PXE Support
I/O Ports	PS/2 Keyboard-1, PS/2 Mouse-1, RJ 45 - LAN port-1, VGA Port-1, USB Port (2.0)-4, Serial Port-2, Parallel Port-1
Optional Support	Open office, Thunderbird Mail client, Emulation Suite, NX Client, SM player
OS Compatibility	Citrix Compatible Operating Systems, Microsoft Windows 2000, 2003 and 2008 Server with Terminal Services, UNIX and LINUX servers
Browser	Firefox Mozilla Browser 2.x/3.x
Expansion Slots	1 PCI slot
Power Supply	External Power Supply
Audio	Local 6 channel mode for 5.1 Speaker output. Local microphone input
Keyboard & Mouse	HCL PS/2 Mechanical/Membrane Keyboard. HCL PS/2 2 Button Scroll/Optical Mouse
Monitors	Choice of HCL TFT-LCD Monitors 15.6" or above
Manageability	HCL Embedded Device Management Software.
Multi Level Security	Admin/User password Change option. Enabling/Disabling Serial Port, Parallel Port, USB port, and USB mass storage devices through BIOS.
Industry Compliance	PCI & ACPI, RoHS
Certificate	ISO 9001:2008