

ITEMS	SPECIFICATIONS
Model	HCL WINBee 5000 VX / HCL WINBee 5000-WES VX
Operating System	Genuine Windows XP Embedded SP3/ Genuine Windows Embedded Standard 2009
Chipset	VIA CN896
Processor	VIA C7 1.6GHz
System Memory	Single DDR Slot which supports 1GB DDR 2 RAM upgradable upto 2GB.
Video Graphics	32 MB Shared VRAM
IDE Channel	2 IDE 40 Pin, Each IDE supports 4 GB
Hard Disk Drive	1 GB IDE Flash, Supports upto 4 GB
Protocol Support	RDP, ICA, Telnet
Network Interface	10/100/1000Mbps BaseT Fast Ethernet, twisted pair (RJ-45), TCP/IP with NETBIOS, DNS, DHCP, WINS. Point-to-Point Protocol (PPP), Point-to-Point over Ethernet (PPPoE), PXE Support, Simple Network Time Protocol (SNTP), Simple Network Management Protocol (SNMP)
I/O Ports	PS/2 Keyboard-1, PS/2 Mouse-1, RJ 45 - LAN port-1, VGA Port-1, DVI Port – 1, USB Port (2.0)-4, Serial Port-2, Parallel Port-1
Optional Support	Emulation Suite, Internal / External Wireless LAN
OS Compatibility	Citrix Compatible Operating Systems, Microsoft Windows 2000, 2003 and 2008 Server with Terminal Services, UNIX and LINUX servers
Browser	Internet Explorer 6.0/Internet Explorer 7.0 [#] /Internet Explorer 8.0 ^{##}
Expansion Slots	1 PCI slot
Power Supply	External Power Supply
Audio	Local 6 channel mode for 5.1 Speaker output. Local microphone input
Keyboard & Mouse	HCL PS/2 Mechanical/Membrane Keyboard. HCL PS/2 2 Button Scroll/Optical Mouse
Monitors	Choice of HCL TFT-LCD Monitors 15.6" or above
Manageability	HCL Embedded Device Management Software.
Multi Level Security	Admin/User password Change option. Enabling/Disabling Serial Port, Parallel Port, USB port, and USB mass storage devices.
Industry Compliance	PCI & ACPI, RoHS
Certificate	ISO 9001:2008

-Available in both HCL WINBee 5000VX & HCL WINBee 5000 WES VX

-Available only in HCL WINBee 5000 WES VX