

ITEMS	SPECIFICATIONS
Model	HCL WINBee 5000 IX / HCL WINBee 5000-WES IX
Operating System	Genuine Windows XP Embedded SP3 / Genuine Windows Embedded Standard 2009
Chipset	Intel NM10 Express Chipset
Processor	Intel Atom 1.8GHz Processor
System Memory	Two DDR 3 SODIMM slot supports upto 4GB, Each slot supports 2GB
Integrated Graphics	Intel Graphics Media Accelerator 3150 integrated graphics subsystem with support for analog displays (Analog)
SATA DOM	Two SATA Ports Each supports upto 4GB
Hard Disk Drive	1 GB SATA Flash upgradable upto 4GB
Protocol Support	RDP, ICA, Telnet
Network Interface	10/100 BaseT Fast Ethernet, twisted pair (RJ-45), TCP/IP with DNS and DHCP, Point-to-Point Protocol (PPP), Direct Connection through RS-232, Point-to-Point over Ethernet (PPPoE), Point-to-Point Tunneling Protocol (PPTP), Layer-2 Tunneling Protocol (L2TP), PXE Support, Server Network Time Protocol (STNP), Simple Network Management Protocol (SNMP)
I/O Ports	PS/2 Keyboard-1, PS/2 Mouse-1, RJ 45 - LAN port-1, VGA Port-1, USB Port (2.0)-6 , Serial Port-1, Parallel Port-1
Optional Support	Emulation Suite, Internal/External Wireless LAN
OS Compatibility	Citrix Compatible Operating Systems, Microsoft Windows 2000, 2003 and 2008 Server with Terminal Services, UNIX and LINUX servers
Browser	Internet Explorer 6.0/Internet Explorer 7.0 [#] /Internet Explorer 8.0 ^{##}
Expansion Slots	1 PCI slot
Power Supply	External Power Supply
Audio	Local 6 channel mode for 5.1 Speaker output. Local microphone input
Keyboard & Mouse	HCL PS/2 Mechanical/Membrane Keyboard. HCL PS/2 2 Button Scroll/Optical Mouse
Monitors	Choice of HCL TFT-LCD Monitors 15.6" or above
Multi Level Security	Admin/User password Change option. Enabling/Disabling Serial Port, Parallel Port, USB port, and USB mass storage devices.
Industry Compliance	PCI & ACPI, RoHS
Certificate	ISO 9001:2008

-Available in both HCL WINBee 5000IX & HCL WINBee 5000 WES IX

-Available only in HCL WINBee 5000 WES IX