



HCL WINBee 4000 BVX

HCL

HCL WINBee 4000 BVX

ITEMS	SPECIFICATIONS
Model	HCL WINBee 4000 BVX
Operating System	HCL Beelin LINUX
Chipset	VIA Cn896
Processor	VIA C7 1GHz
System Memory	Single DDR Slot which supports 512MB DDR 2 RAM upgradable upto 2GB
Video Graphics	32 MB Shared VRAM
IDE Channel	2 IDE 40 Pin
Hard Disk Drive	512 MB IDE Flash, Supports upto 2 GB
Protocol Support	RDP, ICA, Telnet, Optional Terminal Emulation Support
Network Interface	10/100 Mbps BaseT Fast Ethernet, twisted pair (RJ-45)
I/O Ports	PS/2 Keyboard-1, PS/2 Mouse-1, RJ 45 - LAN port-1, VGA Port-1, USB Port (2.0)-4 , Serial Port-2, Parallel Port-1
Optional Support	WLAN Module Support, Open office
OS Compatibility	Citrix Compatible Operating Systems, Microsoft Windows 2000, 2003 and 2008 Server with Terminal Services, UNIX and LINUX servers
Browser	Firefox Mozilla Browser 2.x/3.x
Expansion Slots	1 PCI slot
Power Supply	External Power Supply
Audio	Local 6 channel mode for 5.1 Speaker output. Local microphone input
Keyboard & Mouse	HCL PS/2 Mechanical/Membrane Keyboard. HCL PS/2 2 Button Scroll/Optical Mouse
Monitors	Choice of HCL TFT-LCD Monitors 15.6" or above
Manageability	HCL Embedded Device Management Software
Multi Level Security	Admin/User password Change option. Enabling/Disabling Serial Port, Parallel Port, USB port, USB mass storage devices through BIOS
Industry Compliance	PCI & ACPI, RoHS
Certificate	ISO 9001:2008

For more details:
 E-mail: infiniti@hcl.in
 Phone: +91-120-2555109

HCL